

# HiSOLO

## Solar Light Trailer Tower



### SPECIFICATION

BL2P-600W	
LED Lights	4 × 100W(150lm/W)
Electrical rotation/tilting	optional
Timing/dimming function	optional
Solar Panel	2 × 600W
Panel rotation	235°
Panel Lifting	30°/40°/50°/60°
Battery	4 × 250Ah DC12V
Battery Capacity	12000Wh 80% DoC
System Voltage	DC24V
Battery Charger	1.5KW, 15A
Controller	50A MPPT
Mast & Height	6 Section 7/9M
Mast Lifting	Manual/Electric Winch
Trailer Standard	US / AU / EU
Hitch	2" Ball / 3" Ring
Brake	Electric
Axle	Single
Tire	14 inch
Outriggers	4 ×
Lifting Ring	4 ×
Forklift Holes	6 ×
Working Temp	-35°C~60°C
Charging Time	8.0 hours
Running Time	24 hours for 400W
Dimension(mm)	3778*1675*3175
Weight	1250kgs
QTY in 20' / 40'	6 units / 14 units

### CUSTOMIZED OPTIONAL



LFP Battery



Victron



AL-KO



Skid Type

### CONTAINER LOADING

20' | 6 units

40' | 14 units

